



Technical data

V-BIO	Length [mm]	Width [mm]	Height [mm]	Capacity [m ²] approx.	Max. payload [kg]	Dosing augers	Recomm. gear motor for EnergySave auger
8-1S	3500	2150	2420	8	4000	1	1x15 kW
10-1S	3800	2150	2830	10	5000	1	1x15 kW
12-1S	3800	2150	3130	12	6000	1	1x22 kW
14-1S	4200	2450	2700	14	7000	1	1x22 kW
16-1S	4200	2450	3000	16	8000	1	1x22 kW
18-1S	4200	2450	3300	18	9000	1	1x30 kW
25-2S	6600	2450	2700	25	12500	2	2x22 kW
30-2S	6600	2450	3000	30	16000	2	2x22 kW
35-2S	6600	2450	3000	35	17500	2	2x22 kW
38-3S	9000	2450	2700	38	19000	3	3x22 kW
45-3S	9000	2450	3000	45	22500	3	3x22 kW
50-3S	9000	2450	3300	50	25000	3	3x22 kW
60-3S	9000	3000	3600	60	30000	3	3x30 kW
80-3S	9000	2850	4300	80	40000	3	3x37 kW
V-BIO Combi	Width [mm]	Width [mm]	Height [mm]	Capacity [m ²] approx.	Max. payload [kg]	Dosing augers	Recomm. gear motor for EnergySave augers + hydraulics
60	11000	2500	3900	57	30000	1	1x22 kW + 1x3 kW
80-2D	15000	2500	3500	80	40000	1	1x22 kW + 2x3 kW
100-2D	15000	2500	3900	100	50000	1	1x22 kW + 2x3 kW